



## Roma-door type BDD-40-FC

### Application

The Roma-swing door type BDD-40-FC is a functional, robust and low-maintenance rebated pass door for application in foodcare and conditioned rooms with slight temperature variations.



#### Doorleaf

Foamed doorcase:

Covering	: both sides sendzimir galvanised steelplate, Thickness 0,70 mm.
Finishing	: hard pvc foil, 150 mu, in color RAL 9001.
Thickness	: 40 mm.
Insulation	: PUR-hardcore foam, volume weight approx. 45 kg/m <sup>3</sup> , U-value 0,469 W/(m <sup>2</sup> .K)

#### Frame

Installation	: built in Roma-sandwichpanel wall with door jambs and counter jambs.
Frame	: stainless steel profile welded in the corners and equipped with black hard plastic thermal bridge block.

#### Door fittings

Hinges	: stainless steel lift-off hinges.
Sealing	: rebate door with rubber sealing strip under doorleaf.
Openers	: at both sides stainless steel door handles with door shields. In double leaf version "stainless steel look" espagnolette locking on fixed leaf.
Lock	: including cilinder lock (euro cilinder).
Draairichting	: DIN left or DIN right (in double leaf version pass through leaf at right side).

#### Options with extra charge

- Doorleaf in stainless steel 304 with circular brush finish.
- Stainless steel window frame with insulated float glass 4-15-5 on both sides anti-splinter foil, sizes 400 x 600 mm high.
- Door spring, type Ivana 1670 aluminum with sliding arm.
- Sill profile for installation outside.
- Stainless steel kickplates at lower side doorleaf.
- Stainless steel espagnolette locking for double leaf version.
- Alternative and additional door fittings (a.o. flush fitting cilinders, knobcilinder, free-occupied closing, electric strike).
- Rubber sealing profile on frame.
- Lower door sill.

**roma**  
isolatiesystemen

